


## Flag terminals

### Non-insulated flags



Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
AB14-6A	100	22-14	#6	ERG4004	0.55	0.31	0.22	0.39	0.03
AB51	1,000	22-14	#6	ERG4004	0.55	0.31	0.22	0.39	0.03
AB14-8A	100	22-14	#8	ERG4004	0.55	0.31	0.22	0.39	0.03
AB52	1,000	22-14	#8	ERG4004	0.55	0.31	0.22	0.39	0.03
AB14-10A	100	22-14	#10	ERG4004	0.55	0.31	0.22	0.39	0.03
AB53	1,000	22-14	#10	ERG4004	0.55	0.31	0.22	0.39	0.03
C51	500	12-10	#6	ERG4004	0.66	0.31	0.25	0.48	0.04
C10-8A	50	12-10	#8	ERG4004	0.66	0.31	0.25	0.48	0.04
C52-TB	500	12-10	#8	ERG4004	0.66	0.31	0.25	0.48	0.04
C10-10A	50	12-10	#10	ERG4004	0.66	0.31	0.25	0.48	0.04
C53-TB	500	12-10	#10	ERG4004	0.66	0.31	0.25	0.48	0.04
D236	200	8	#10	WT129	0.83	0.50	0.25	0.59	0.06
D226	200	8	#10	WT129	0.90	0.50	0.29	0.64	0.06
D271	200	8	¼	WT129	0.92	0.50	0.33	0.68	0.06
E226	200	6	#10	WT129	0.93	0.50	0.29	0.69	0.06
E271	200	6	¼	WT129	0.99	0.50	0.33	0.73	0.06
E272	200	6	⅜	WT129	1.05	0.50	0.41	0.81	0.06
F226	200	4	#10	WT129	1.07	0.56	0.33	0.80	0.07
F271	200	4	¼	WT129	1.10	0.63	0.33	0.80	0.07
F272	200	4	⅜	WT129	1.18	0.63	0.41	0.88	0.07
F273	200	4	⅝	WT129	1.20	0.63	0.43	0.90	0.07
G671	100	2	¼	WT129	1.20	0.63	0.33	0.89	0.08
G672	100	2	⅜	WT129	1.28	0.63	0.41	0.97	0.08
G673	100	2	⅝	WT129	1.32	0.63	0.46	1.02	0.08
H672	50	1/0	⅜	13642M	1.31	0.63	0.41	1.01	0.10
H673	50	1/0	⅝	13642M	1.36	0.63	0.46	1.06	0.10
J672	50	2/0	⅜	13642M	1.46	0.75	0.41	1.10	0.10
J673	50	2/0	⅝	13642M	1.51	0.75	0.46	1.15	0.10
J675	50	2/0	½	13642M	1.67	0.75	0.55	1.24	0.10
K672	50	3/0	⅜	13642M	1.59	0.81	0.41	1.19	0.11
K673	50	3/0	⅝	13642M	1.64	0.81	0.46	1.24	0.11
K675	50	3/0	½	13642M	1.76	0.81	0.55	1.34	0.11
M673	50	250 kcmil	⅜	13642M	1.89	1.0	0.46	1.43	0.13
M675	50	250 kcmil	½	13642M	1.99	1.0	0.55	1.52	0.13

Diagram

